

PRODUCT SPECIFICATION

HMK® S244 - COLOR ENHANCER - extra

- **Protection and care for all natural stone surface finishes (including polished) as well as artificial stone surfaces.**
 - **Reduces the penetration of water, dirt, oil, and grease.**
- **The color and structure of the surface will be significantly enhanced.**
 - **For interior and exterior use.**
 - **Food hygiene compliant.**

HMK® S244 is a ready to use special impregnator which reduces the penetration of water, dirt, oil and grease into all natural stone surfaces (soft and hard stones), agglomerates and terrazzo. For interior and exterior use. HMK® S244 can be used on polished, honed and textured surfaces. The color and structure of the surface will be significantly enhanced.

Instructions: If under floor heating exists, make sure it is turned off at least two days before application to allow the surface to cool. Clean the area to be treated thoroughly and allow it to dry (max. residual moisture of 2 to 4%). Apply HMK® S244 generously and evenly using a soft paintbrush, roller with short fibres or HMK® Z950-Z951 Application Brushes. Repeat treatment for very absorbent surfaces after 24 hours. For less absorbent surfaces, remove excess with a paper towel before it dries. Smears left after the application process can be loosened and wiped off by using a soft clean cloth moistened with some more HMK® S244.

To clean surface thoroughly before treatment, use HMK® R155 Intensive Cleaner - acid free.

For regular cleaning and continued protection use HMK® P324 Liquid Stone Soap, a no-rinse natural product.

Once dry the residual material is not hazardous to health and is approved for use with foodstuffs by the LFGB (German Food and Feed Code).

Drying time: Dependent upon room temperature and ventilation, around 2 to 4 hours.

Important: Do not walk on the treated surface until treatment is complete. Protect surface from rain and humidity for 12 hours. Do not apply to rubber, plastics, lacquered or varnished surfaces and solvent intolerant materials. Remove all foodstuffs from the area to be treated before work is commenced.

Coverage: About 5-20m²/litre.

Warning: Chemical product. Contains turpentine substitute. Flammable. Keep away from heat, sparks and flame. Harmful or fatal if swallowed or inhaled. Ensure the area to be treated is adequately ventilated. Avoid eye/skin contact. If exposed wash/flush with water and seek medical attention immediately. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

Packaging: 12 x 1 litre bottles/box; 2 x 5 litre cans/box; 2 x 10 litre cans/box.

Storage: Store in a cool place and keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.